ZIMFLEX
industrial hoses

Light grey soft PVC dust suction hose

Product images	Application	Characteristic	Structure
	►Smoke suction and exhaust	►Lightweight and soft	►Color: Grey
	►Dust suction and exhaust	►Excellent bending performance	►Temperature: -10°C / +50°C
	►Sawdust suction and discharge	►Smooth inner wall	►Standard:
	►Vacuum cleaning equipment	►Aging resistance	Compliant with ROHS 2011/65/EC directive
		►Ozone resistant	
		►Wear resistant and torsion resistant	
►Hose wall: PVC			
►Reinforcement: PVC plastic reinforcement			

Part Number	Internal Diameter mm	Outer Diameter mm	Wall thickness mm	Coild Length m
951L-025-50	25.0	31.0	0.8	20
951L-030-50	30.0	36.0	0.8	20
951L-032-50	32.0	38.0	0.8	20
951L-035-50	35.0	41.0	0.8	20
951L-038-50	38.0	44.0	0.8	20
951L-040-50	40.0	45.0	0.8	20
951L-045-50	45.0	51.0	0.8	20
951L-050-50	50.0	58.0	1	15
951L-051-50	50.8	59.0	1	15
951L-060-50	60.0	68.0	1	15
951L-063-50	63.5	71.5	1	15
951L-065-50	65.0	73.0	1	15
951L-070-50	70.0	78.0	1	15
951L-075-50	75.0	83.0	1.5	15
951L-076-50	76.2	84.2	1.5	15
951L-080-50	80.0	88.0	1.5	15
951L-090-30	90.0	98.0	1.5	15
951L-100-30	100.0	112.0	2	10
951L-102-30	102.0	114.0	2	10
951L-110-30	110.0	122.0	2	10
951L-120-30	120.0	132.0	2	10
951L-125-30	125.0	137.0	2	10
951L-127-30	127.0	139.0	2	10
951L-130-30	130.0	142.0	2	10
951L-140-30	140.0	152.0	2	10
951L-150-20	150.0	162.0	2	10
951L-152-20	151.5	163.5	2	10
951L-152-20	152.4	164.4	2	10
951L-160-20	160.0	172.0	2	10
951L-180-20	180.0	192.0	2	10
951L-200-20	200.0	214.0	2	10
951L-203-20	203.2	217.2	2	10
951L-250-10	250.0	264.0	2	10
951L-300-10	300.0	314.0	2	10

*Note: * All technical parameters are approximate values and measured under conditions of 23 ℃ operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.*

** We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.*